

## BN 20900

## DOUBLE SIDED TAPE

Double sided TNT tape with acrylic adhesive and siliconized paper liner. High adhesion level and very good high temperature resistance.

### MAIN APPLICATIONS AND ADVICES FOR THE CORRECT TAPE USE

- High performance tape for all splicing
- For holding and laminating operations in cardboard and paper industries
- Especially suitable for heavy paper or corrugated board

### TECHNICAL DATA

|                   |                                    |
|-------------------|------------------------------------|
| CARRIER           | Cellulose fiber tissue             |
| LINER             | White siliconized paper            |
| ADHESIVE          | Acrylic                            |
| COLOR             | Clear                              |
| TOTAL THICKNESS   | 130 $\mu$ m (AFERA 4006-ED.9/79)   |
| HEAT RESISTANCE   | 190 °C (internal method PS-QUA-14) |
| ADHESION TO STEEL | 600 cN/cm (AFERA 4001-ED.10/87)    |

### WARRANTY

The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

The technical information and data, recommendations, and other statements provided in this document are based on Novacel tapes tests or experience. It will be up to the user matching the product with the working process or surface. Novacel tapes will not be, at any rate, held responsible for not proper use. Warranty is limited to replacement of products that Novacel tapes proves to be defective and keeps out any other damages.