

BN 3110

Q2-SPLICE

Self-splittable double coated tape, with a metallized paper laminate carrier, for flying splices on coldset web offset presses in the newsprint industry. It can be used on different paper weights and thicknesses. Aluminized backing for splice inductive detection.

MAIN APPLICATIONS AND ADVICES FOR THE CORRECT TAPE USE

For flying splices on coldset web offset presses in the newsprint industry.

TECHNICAL DATA

CARRIER	Paper-metallized paper laminate
LINER	White siliconized paper
ADHESIVE	Modified acrylic
COLOR	Green
TOTAL THICKNESS ⁽¹⁾	110 μ m (AFERA 4006-ED.9/79)

(1) it refers only to the splicing part of the tape

WARRANTY

The tape can be stored for maximum 8 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.

The technical information and data, recommendations, and other statements provided in this document are based on Novacel tapes tests or experience. It will be up to the user matching the product with the working process or surface. Novacel tapes will not be, at any rate, held responsible for not proper use. Warranty is limited to replacement of products that Novacel tapes proves to be defective and keeps out any other damages.