NOVACEL
Beyond The Surface

TECHNICAL DATA SHEET

BN 3510 Q2-SPLICE

Self-splittable double coated tape for flying splices of filmic materials in converting, laminating and flexographic printing process. Suggested for high slip films.

MAIN APPLICATIONS AND ADVICES FOR THE CORRECT TAPE USE

- Flying splices in flexographic printing
- Flying splices in converting

TECHNICAL DATA

CARRIER	Paper laminate
LINER	White siliconized paper
ADHESIVE	Synthetic rubber and resins
COLOR	Blue
TOTAL THICKNESS(1)	140 μm (AFERA 4006-ED.9/79)

(1) it refers only to the splicing part of the tape

WARRANTY

The tape can be stored for maximum 12 months from the date of production in dry conditions and in its original packaging. The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position.
The technical information and data, recommendations, and other statements provided in this document are based on Novacel tapes tests or experience. It will be up to the user matching the product with the working process or surface. Novacel tapes will not be, at any rate, held responsible for not proper use.
Warranty is limited to replacement of products that Novacel tapes proves to be defective and keeps out any other damages.